
6 mm LED modul FinePitch k použití v interiéru

NEC LED-06AF1 (6 mm Indoor)





The NEC 6mm indoor LED module with its light weight is designed to meet the demanding requirements of the rental market on the one hand and fixed installation, because of the low power consumption.

The NEC LED Solutions product for rental/staging as well as indoor retail signage market segment for nearer viewing application/venues and very bright environments.

Výhody

LED displays – are the perfect solution to direct messages to the audience with far viewing distance.

Total cost of ownership reduction – with long-life LED lamp made by [value1], which creates the longest LED life available for a video wall.

Great contrast – by using industry-leading contrast black LED and improved shader.

Even in bright environments of modern architectures LED – with its high brightness is still able to impress the audience.

ONE SOURCE DISPLAY SOLUTIONS – NEC Leadership and large Display Portfolio enables the customer to reduce the cost of purchase as all retail signage display technologies are available from NEC Display Solutions.

Specifications

Informace o výrobcích

Název výrobku
NEC LED-06AF1 (6 mm Indoor)

Skupina produktů
6 mm LED modul FinePitch k použití v interiéru

Objednací kód
60003000

Display

Pixel Configuration
3 v 1 SMD (černé)

Rozteč bodů [mm]
6.25

Kontrastní poměr (typ.)
3500:1

Pozorovací úhly [°]
75/75 horizontal / 70/70 vertical

Jas (max.) [cd/m²]
2000

Dimming Capability
64 levels

Colour Processing
14 bit

LED Refresh Rate [kHz]
19.2

Colour Temperature [K]
3200; 5000; 6500 (default); 7500; 9300

Gamma Correction
1.8; 2; 2.2 (default); 2.4

Rozlišení obrazovky

Počet pixelů na m²
160 x 160

Rozlišení v pixelech na modul [dot]
80 x 80

Connectivity

Digital Video in / out
DVI Connector; DVI with RS-422

Power in / out
Circular Connector

Electrical

Spotřeba energie typ. [W]
235W (full white); 78W (50% gray level)

Power Requirements
100-20 V/220-240 V; 3 A/1.5 A; 50/60 Hz; internal power supply

Environmental Conditions

Operating Temperature [°C]
-20 to 40

Operating Humidity [%]
10 to 90

Storage Temperature [°C]
-30 to 60

Storage Humidity [%]
10 to 90

Mechanical

Rozměry (W x H x D) [mm] na modul
499,7 x 499,7 x 170,3

Hmotnost [kg]
12.7 per sqm

Regulační podmínky

Bezpečnost a ergonomie
CE; FCC Class A; RoHS

Další funkce

IP Level
IP2

Certifications
C-tick; GOST; SASO; TÜV GS; UL; VCCI

Warranty
2 years



CE



FCC Class A



RoHS

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers.
All specifications are subject to change without notice. Errors and omissions are excepted. 24.09.2026