

This is Why



- ▶ FANLESS AND NOISELESS MODULAR RETAIL AND FAST FOOD POS SYSTEM
- ▶ LARGE 38 CM TRUE FLAT COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ HIGH VISIBLE ADJUSTABLE LEFT/RIGHT AND UP/DOWN LED BACKLIGHT LCD TOUCH SCREEN
- ▶ SUPERIOR EASY TO CLEAN AND HIGH IP RATING LCD FRONT PANEL
- ▶ 10/100/1000 BASE ETHERNET CONNECTION
- ▶ HARD DISK SUPPORTS SMART (SELF MONITORING/ANALYSIS AND REPORTING TECHNOLOGY)
- ▶ WEPOS READY 2009 PRE-INSTALLED

Especially small and mid size companies must be highly flexible to survive in their daily business against larger companies. With the need of being active in the retail and fast food market, the flexible PC-based POS terminal RZ-X750FV4 offers a lot of additional opportunities, as it allows to install specific application software dedicated to the market segments. Apart from this, the RZ-X750FV4 can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26,4 cm LCD customer display, magnet card reader etc. Not only visually, but also from the daily work and efficiency standpoint the RZ-X750FV4 is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X750FV4 reduces energy cost to a significant low level.

DISPLAY

- ▶ Barevný odstín (cm): **38**
- ▶ TFT barevné LCD displej: ✓
- ▶ Nastavitelná velikost (body): ✓
- ▶ Velikost 1: **1.024 x 768 (XGA)**
- ▶ Velikost 2: **Not supported**

SÍŤ

- ▶ Ethernet 10 / 100 / 1000 Mbps: ✓/✓/✗

TECHNICKÉ SPECIFIKACE

- ▶ Rozměry (Š x V x H mm): **365 x 234 x 360**
- ▶ Hmotnost (kg): **6.5**
- ▶ Spotřeba energie Provoz (W): **max. 180 (without peripherals)**
- ▶ EMV Class: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

PC SYSTÉM

- ▶ Operační systém: **WEPOS Ready 2009**
- ▶ CPU: **Intel ATOM 1.8 GHz (D525)**
- ▶ L1 Cache: **L1 D-Cache: 48KB (24KB X 2)L1 I-Cache: 64KB (32KB X 2)**
- ▶ L2 Cache: **1MB (512KB X 2)**
- ▶ BIOS ROM (Flash ROM): **AMI SHARP**
- ▶ Standardní RAM Paměť: **2 GB**
- ▶ Maximum RAM Paměť: **4 GB**
- ▶ Pevný disk: **320 GB**
- ▶ Video RAM: ✓
- ▶ Čtečka magnetické karty: **optional**
- ▶ LPT paralelní port: **1**
- ▶ Zákaznický display: **Optional external 2 line customer or 29 cm LCD customer display**
- ▶ Zásuvka: **maximal 2**
- ▶ Konektor telefonu: ✓

PORTY I/O

- ▶ Sériové RS232: **4**
- ▶ USB: **5/1 powered USB**
- ▶ Externí monitor (VGA rozhraní): **1**

www.sharp.cz

SHARP

SHARP ELECTRONICS (EUROPE) GMBH
CENTRÁLA CENTRAL & EASTERN EUROPE
A-1020 Vídeň
HANDELSKAI 342
INFOLINKA: 800 611 008
FAX: +43 1 727 19 239
INTERNET: WWW.SHARP.CZ