Empowered by Innovation

NEC

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors

NEC MultiSync® EA191Me





product design award 2009

Fully featured office monitors with outstanding ecological performance and display quality

- Highly efficient panel technology with only 2 backlights saves more than 30 % energy
- Ecologics and Ergonomics complying to the latest standards incl. EPEAT Gold
- ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey

see more.

NEC Display Solutions

NEC MultiSync® EA191Me

TECHNICAL SPECIFICATIONS

Panel Technology	TN TFT
Screen Size [inch/cm]	19,0 / 48,2
Pixel Pitch [mm]	0.294
Viewing Angle [°]	178 horizontal / 170 vertical (typ. at contrast ratio 10:1) 178 horizontal / 170 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	1000:1
Brightness (typ.) [cd/m²]	250
Response Time (typ.) [ms]	4
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	30 - 82
Vertical Frequency [Hz]	56 - 75
Optimum Resolution	1280 x 1024 at 60 Hz
Supported Resolutions	1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D (with HDCP); Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; DV Mode; EcoMode; Fine Adjust (analog); Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Power-Off Timer; sRGB
Safety and Ergonomics	EPEAT Silver™; EPEAT™ Gold (black version); CE; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Consumption on Mode [W]	25 (typ.); 18 (Eco Mode)
Power Consumption Power-Saving Mode [W]	< 0,5
Power Supply	100-120 V/220-240 V; 1,0 A/0,5 A; integrated power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	20 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height adjustable Stand [mm]	110
Screen Tilt / Swivel / Rotate [°]	-5 to 15 / -45 to 45 / 0 to 90 (landscape to portrait mode)
Dimensions (W x H x D) [mm]	408,0 x 383,5 x 220,0
Bezel Width [mm]	15,0
Weight [kg]	7
Cable Management	yes
Kensington Lock	yes
Benefits	16:10 wide format; Carbon Footprint Meter; Carbon Savings Meter; NaViSet®and NaViSet®Administrator compatible; sRGB Support; TORO™ Design; WindowsVistaCertifiedLogo
Audio Functions	1W + 1W (De-activateable)
Colour Versions	Silver Front Bezel; White Back Cabinet Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable VGA - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 06/09

www.nec-display-solutions.com

NEC Display Solutions Europe GmbH