Empowered by Innovation

NEC

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors

NEC PlasmaSync® 42XP10



Professional Plasma Public Displays with brilliant colours - especially for dynamic screen content.

- 42" XGA resolution with aspect ratio 16:9
- Enhanced TileMatrix split screen function for variable video walls
- Zoom navigation and timer function
- Comfortable ticker function for simultaneous information display
- 1080p and 24p compatible

see more.

NEC Display Solutions

NEC PlasmaSync® 42XP10

TECHNICAL SPECIFICATIONS

Screen Size [inch/cm]	42 / 106,7
Native Resolution [pixels]	1024 x 768
Active Screen Area (W x H) [mm]	921,5 x 519,0
Aspect Ratio	16:9
Viewing Angle [°]	Over 160
Contrast Ratio (typ.)	15000:1
Brightness (typ.) [cd/m²]	1500
Real Colour Reproduction	1 billion colours, 1024 steps (10 bit)
Digital Zoom [%]	100 - 900 (selectable)
Picture Modes	Bright / Normal / Theatre 1 / Theatre 2 / Default
Enhanced Split Screen	PIP (4 modes); Side by Side (6 modes); Sub Picture Detect / Fade / Transparency; Text Insert
Motion Compensated 3D Scan Converter	PAL; NTSC; 480i; 576i; 525i; 625i; 1035i; 1080i
Complete Progressive Support	576p at 50Hz; 480p at 60Hz; 720p at 50/60Hz; 1080p at 24/25/30/50/60Hz; PC: W-UXGA (1920 x 1200 max)
Noise Reduction	NR-1, NR-2, NR-3
Aspect Mode	Normal; Zoom; Full; Dynamic; True; 2.35:1; 14:9; Underscan
PDP Screensaver	PLE (3 modes); Inverse; White; Orbiter (5 modes)
Tuner	Optional
Composite 1	1 x BNC
Composite 2	1 x RCA
S-Video	1 x 4 pin Din
SCART 1	RGBs (via Adapter at RGB2) (DVD/HD1 and RGB inputs support different signals)
SCART 2	RGBs (via Adapter at RGB1) (DVD/HD1 and RGB inputs support different signals)
Component 1	1 x RCA (Y, Pb[Cb], Pr[Cr])
Component 2	1 x RCA (Y, Pb[Cb], Pr[Cr])
PC (RGB)	1 x 15 pin D-Sub (RGBHV/RGBs); 1 x BNC (RGBHV/CS,V)
DVI-D / HDMI	1 x DVI-D (with HDCP) / -
Video Output	BNC Composite or 15 pin D-Sub (selectable) (Video1 and RGB1 can be used also as outputs (Daisy Chain))
Audio	1 x RCA Phono (L+R)
Speaker Output	8 + 8 W at 8 Ω
Front Panel User Controls	Power ON/Standby, Audio Mute, Input Select/(Set), +/(Right), -/(Left), Up, Down, Exit/Menu
Serial Communication	1 x D-Sub 9 pin Serial (RS-232C, In/Out); Daisy Chain; AMX Café Duet
Power Supply	100 to 240 V at 50/60Hz
Power Consumption (typ.) [W]	300
Current Rating (max.) [A]	4,2
Dimensions (W x H x D) [mm]	1036 x 644 x 127
Net Weight [kg]	Without stand: 33,5; With stand: 37,0
Temperature [°C]	+0 to +40 (operating) / -10 to 50 (storage)
Humidity [%]	20 to 80 (operating) / 10 to 90 (storage) - non-condensing
Altitude [m]	0 to 2000 (6160 feet, operating) / 0 to 3000 (9510 feet, storage)
Safety and Ergonomics	CE; RoHS; TÜV GS
Options	Speakers; Stand
Special Features	2 x 2/3 x 3/4 x 4/5 x 5/ 2 x 1/3 x 1/4 x 1/5 x 1/1 x 2/1 x 3/1 x 4/1 x 5 Video Wall Function; 3-2/2-2 Pull-down Converter; 3D Scan Converter; Auto Luminance Management; Auto Picture; Burn In Reduction Tools; Colour Tune; Control Lock; Digital Zoom; Gamma Correction; Loop Through Interface; Overheating Protection; Programmable Timer; Text Ticker Function; Zoom Navigator

The plasma display screen, also called „panel", is comprised of tiny image elements (cells). Although NEC manufactures these plasma displays with 99.99 % of their cells active, individual cells may occasionally produce no light or remain lit when they should have turned off. The brightness of a plasma display declines during the course of the unit's lifetime. Static images should not be displayed over a longer period of time, as this may cause phosphor burn on certain areas of the screen. Phosphor burn is not covered by the warranty. Please note our terms and conditions of our guarantee at www.nec-display-solutions.com.

PlasmaSync® and OSM are registered trademarks of the NEC Corporation. Technical modifications excepted. Status: 03/09

www.nec-display-solutions.com

NEC Display Solutions Europe GmbH