Empowered by Innovation

NEC

LCDs • Projectors • Plasmas • LCDs • Projectors • Plasmas • LCDs • Projectors

NEC MultiSync® E221W





see more.

NEC Display Solutions

Entry-level wide (16:10 format) office monitors - offering great flexibility and strong ergonomic features.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- ErgoDesign®: Height adjustable stand (50 mm)
- Safety of investment with analog/digital interface and HDCP
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey
- Low energy consumption with Eco Mode and unique Carbon Savings Meter

NEC MultiSync® E221W

TECHNICAL SPECIFICATIONS

Panel Technology	TN TFT
Screen Size [inch/cm]	22,0 / 55,9
Pixel Pitch [mm]	0.282
Viewing Angle [°]	160 horizontal / 160 vertical (typ. at contrast ratio 10:1) 176 horizontal / 176 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	1000:1
Brightness (typ.) [cd/m²]	250, (300 max)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	30 - 82
Vertical Frequency [Hz]	56,0 - 75,0
Optimum Resolution	1680 x 1050 at 60 Hz
Supported Resolutions	1680 x 1050; 1440 x 900; 1400 x 1050; 1360 x 768; 1280 x 1024; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 640 x 480
Connectors	Digital: 1 x DVI-D (with HDCP); Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; DV Mode; EcoMode; Fine Adjust (analog); Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Power-Off Timer; sRGB
Safety and Ergonomics	EPEAT Silver™; CE; ERP; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; FCC Class B; PCT/ Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Consumption on Mode [W]	40 (typ.); 28 (Eco Mode)
Stand-by Mode [W]	2
Power Supply	100-120 V/220-240 V; 1,0 A/0,5 A; integrated power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	20 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height adjustable Stand [mm]	50
Screen Tilt / Swivel / Rotate [°]	-5 to +30 / -170 to +170
Dimensions (W x H x D) [mm]	508 x 374 x 240
Bezel Width [mm]	16,0
Weight [kg]	6,3
Cable Management	yes
Kensington Lock	yes
Benefits	16:10 wide format; Carbon Footprint Meter; Carbon Savings Meter; NaViSet®and NaViSet®Administrator compatible; sRGB Support; WindowsVistaCertifiedLogo
Colour Versions	Silver Front Bezel; White Back Cabinet Black Front Bezel, Black Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable VGA - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 02/10

www.nec-display-solutions.com

NEC Display Solutions Europe GmbH