Preliminary Datasheet

LCD 75" InGlass™Touch Display

NEC MultiSync® M751 IGB non-touch

Benefits

Best-in-class visual performance – benefit from a „pixel-free“ Ultra-High Definition (UHD) visual performance.

Natural writing experience – it’s like working on paper! Whether using finger or pen, the InGlass™ touch technology provides seamless interactive touch performance including Windows Ink and palm rejection.

Featuring NEC Open Modular Intelligence (OMI) slot-in technology – choose scalable computing power with Raspberry Pi Compute Module 4 or the more powerful Intel® Smart Display Modules (Intel®SDM) for tailor-made solutions.

Mission-critical 24/7 ready operation – the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Be more productive – get a one-year free license of FlatFrog Board for Rooms! FlatFrog Board whiteboard software makes hybrid work easy and equally productive for everyone.

Specifications

Product Information

Product Name
NEC MultiSync® M751 IGB non-touch

Product Group
LCD 75" InGlass™Touch Display

Display

Panel Technology
ADS with Direct LED backlights

Screen Size [inch/cm]
75 / 189.3

Aspect Ratio
16:9

Brightness (without glass) [cd/m²]
500

Contrast Ratio
≥ 8000:1 [1]

Viewing Angle [°]
178 horizontal / 178 vertical (typ. at contrast ratio 10:1)

Colour Depth [bn]
1.073 (10bit)

Colour Gamut
72% of DCI

Response Time (typ.) [ms]
8

Panel Refresh Rate [Hz]
60

Haze Level [%]
Pro (25)

Supported Orientation
Landscape; Portrait

Protective Glass

Type
Premium toughened glass, anti-glare coating

Thickness [mm]
3

Hardness [H]
7

Resolution

Native Resolution
3840 x 2160

Supported Resolutions

1024 x 768;	1440 x 900;	2560 x 1600;
1280 x 1024;	1600 x 1200;	3840 x 2160;
1280 x 720;	1920 x 1080;	4096 x 2160;
1360 x 768;	1920 x 1200;	7680 x 4320
1366 x 768;	1920 x 2160;	
1400 x 1050;	2560 x 1440;	

Synchronisation Rate

Horizontal Frequency [kHz]
15 - 135

Vertical Frequency [Hz]
23 - 76

Connectivity

Input Video Digital
2 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)

Input Audio Digital
1 x DisplayPort; 2 x HDMI

Input Control
LAN 100Mbit; remote control wire (3,5mm jack); RS232

Input Data
1 x USB 2.0 (Downstream); 1 x USB 2.0 (Powered 5V/2A, Firmware Updates); 1 x USB 2.0 Type-B (Downstream)

Output Video Digital
1 x DisplayPort (loop through: DisplayPort, SDM slot-in PC); 1 x HDMI (loop through: HDMI, SDM slot-in PC)

Output Audio Analogue
1 x 3,5 mm jack

Output Control
1 x LAN 100Mbit

Input Detect
Custom; First; Last

PiP/PbP
Dual-Split; Quad-Split; scalable picture size

Calibration

Factory Calibration
Gamma; Intensity; RGB; Uniformity; White Point

Sensor Calibration (through USB)
PC-less Calibration with USB Sensor MDSVSensor3; White Copy (post self-calibration)

Calibration with Software
Corner Uniformity; Gamma; Intensity; RGB; Update Factory Calibration; White Point

Calibration Software
Display Wall Calibrator

Open Modular Intelligence

Intel® SDM
accepts Intel® Smart Display Modules Large and Small up to 66 W

Compute Module Slot
RPi Compute Module 4

Sensors

Temperature Sensor
Integrated, 3 sensors, triggered actions programmable

Electrical

Power Consumption [W]
205 shipping

Power Savings Mode [W]
< 0.5; < 2 (Networked Standby)

Power Management
VESA DPMS

Power Supply
100-240 V AC; 50/60 Hz; internal

Environmental Conditions

Operating Temperature [°C]
+0 to +35

Operating Humidity [%]
20 to 80

Storage Humidity [%]
10 to 80

Storage Temperature [°C]
-20 to 60

Mechanical

Dimensions (W x H x D) [mm]
1,724.6 x 1,003 x 93.4

Weight [kg]
62

Bezel Width [mm]
21.9 (symmetrical)

VESA Mounting [mm]
4 holes; 600 x 400 (FDMI); M8

Ingress Protection
IP5x (front); IP2x (back)

Packaging Dimensions (W x H x D) [mm]
1,830 x 1,070 x 225

Packaging Weight [kg]
75.5

Material
Metal

Available Options

Accessories
Speaker (SP-RM3); Trolley (L20PNSR780MEU, PD02MHA, PD03MHA); Wall mount (L20PNWALL90EU)

Regulatory

Safety and Ergonomics
CE; EMC Class B; RoHS

Pixel Failure Class
ISO 9241-307, Class 1

Green Features

Energy Efficiency
Energy Consumption: 145 kWh/1000 h; LED Backlight

Ecological Standards
EnergyStar 8.0

3rd Party Certifications

Crestron
Certified for Crestron Connected

Additional Features

Special Characteristics
DICOM Simulation; HDMI ARC; Powered USB Port (10 W)

Audio
Integrated Audio Amplifier (for optional speakers up to 2 x 15 W); Integrated Speakers (10 W + 10 W)

Shipping Content
2 x Passive Stylus; 2x AAA batteries; Display; HDMI Cable; Power Cable; Remote Control; Setup Manual; USB cable

Warranty
3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension [2]

Operating Hours
24/7

External Control
AMX NetLinx Support; ASCII Control Commands; Crestron Connected; HDMI CEC; HTTP Browser; PJLink; Scheduled Timer; SNMP

Remote Management
Automated Email Alerts; NaViSet Administrator 2

Security
Disable HW Buttons; Disable IR Functionality; Emergency Notification

[1] out of the box conditions, local dimming ON

[2] please refer to terms and conditions of warranty extensions

RoHS

CE

This document is © 2026 Sharp Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 12.10.2026